

United States Patent [19]

Spiesberger

[11] Patent Number:

5,691,957

[45] Date of Patent:

Nov. 25, 1997

[54] OCEAN ACOUSTIC TOMOGRAPHY
 [75] Inventor: John L. Spiesberger, Port Matilda, Pa.
 [73] Assignee: Woods Hole Oceanographic

Institution, Woods Hole, Mass.

[21] Appl. No.: **792,701**

[22] Filed: Jan. 29, 1997

Related U.S. Application Data

[63]	Continuation of Ser. No. 424,630, Jun. 30, 1994, abandoned.
[51]	Int. Cl. ⁶ G01V 1/00
[52]	U.S. Cl. 367/3 ; 367/5; 367/6; 73/170.29
[58]	Field of Search 367/3, 5, 6; 73/170.29

[56] References Cited

U.S. PATENT DOCUMENTS

OTHER PUBLICATIONS

John L. Spiesberger, et al "Understanding Global Climate Change With Ocean Acoustic Tomography And Models", International Information Forum, State Kremlin Place Moscow, Nov. 23–29, 1992.

John L. Spiesberger, "Listening For Climate Temperature Change In The Ocean", Oceanology International 92 Exhibition and Conference, Brighton, England, Mar. 10–13, 1992

John L. Spiesberger and James B. Bowlin, "A Telemetry Scheme For Ocean Acoustic Tomography: Real Time Monitoring", Journal of Marine Environmental Engineering, vol. 1, pp. 1–22, 1993.

John L. Spiesberger, "Is It Cheaper To Map Rossby Waves In The Global Ocean Than In The Global Atmosphere?", Journal of Marine Environmental Engineering, vol. 1, pp. 83–90, 1993.

John L. Spiesberger, et al, "Global Acoustic Mapping Of Ocean Temperatures (GAMOT)", IEEE Oceans '93 Proceedings, pp. I-253-I-257, 1993.

John L. Spiesberger, "Inland Oceanography?", Earth And Mineral Sciences, vol. 62, No. 3, pp. 51-55, Penn State College.

Daniel E. Frye, et al "Surface Suspended Acoustic Receiver (SSAR) For Mapping Ocean Temperatures", Woods Hole Oceanographic Institution.

Lee Freitag, et al, "Surface Suspended Acoustic Receiver", Sea Technology, Feb. 1995, pp. 43-48.

Primary Examiner—J. Woodrow Eldred
Attorney, Agent, or Firm—Norman E. Brunell

[57] ABSTRACT

An acoustic tomography telemetry system and method allowing spatially averaged ocean temperatures to be measured in real-time. The system includes autonomous acoustic sources mounted on subsurface moorings and receivers that are either suspended from drifting surface buoys or cabled to shore. The telemetry method largely eliminates, in real-time, corruption of acoustic travel times due to wander of the source's mooring by shifting the start times of tomographic transmissions. Corrections to source wander are obtained without expending battery energy over and above that used in conventional tomography experiments. Standard techniques are used to correct clock errors at the source in real-time.

20 Claims, 7 Drawing Sheets

